

elite POS 10.4" Panel Mount LCD



Speaker
Included!

- Vesa Mount
- Base OPTIONAL

REAR VIEW



SIDE VIEW



MAIN SPECIFICATIONS ET-OC104-B

PANEL	
Cell Type	Color active matrix TFT (Thin-Film-Transistor) LCD Panel
Pixel Arrangement	RGB vertical stripe
Glass Surface	Anti-Glare coating
Pixel Number	800(H) x 600(V)
Pixel Pitch	0.264(H) mm x 0.264(V) mm
Display Size	10.4" viewable diagonal area
Active Area	211.2(H) x 158.4(V) mm
Color Depth	262K Colors
Light Source	Long life, 50,000 hours (typ)
Brightness	350 cd/m ²
Contrast Ratio	150:1
Viewing Angle	Horizontal (typ) (L ~ R: -50° ~ +50°), Vertical (typ) (U ~ D: -35° ~ +35°)
INPUT SIGNAL	
Video	Analog RGB (0.7/1.0 Vp-p, 75 ohms)
Sync	Composite Sync
Frequency	Fh: 30 - 82 Khz, Fv: 60 - 75Khz
RESOLUTION	
Supported	1024 x 768 @ 60/70/75 Hz 800 x 600 @ 60/70/75 Hz 640 x 480 @ 60/70/75 Hz 720 x 400 @ 60/70 Hz 640 x 350 @ 70 Hz 800 x 600 @ 60 Hz
Recommended	800 x 600 @ 60 Hz
CONTROL	
Top Back (OSD)	Auto Adjust, Brightness, Contrast, H-Position, V-Position, Phase, Color, Default, Volume, Language, Memory recall
POWER	
Input Voltage	AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A
Power Rating	Operation: 25 Watt, Off: < 5 Watt
OPERATING CONDITION	
Temperature	-10°C ~ 65°C
Humidity	10% ~ 90% (no condensation)
STORAGE CONDITION	
Temperature	-30°C ~ 70°C
Humidity	10% ~ 90% (no condensation)
OTHER	
Audio	2W x 1 Speaker
Dimensions (W x H x D)	264 x 225 x 40.5 mm
Weight (Net/Gross)	3 Kg/4Kg
Options	Video-In: 1 x RCA Connector, 1 x S-Video
Certification	FCC, CE