



# 15" TFT Active Matrix LCD Display

Part Number: ET06-15DRSB



Side View



Rear View



Optional  
"A" Base

Part # ET06-ABSE

## Specifications

LCD Panel	15" TFT Active Matrix LCD Display
Resolution	1024 x 768 Pixels, 16.7M Colors
Contrast Ratio	450:1
Brightness	250 cd/m <sup>2</sup>
Response Time	12 ms
Pixel Pitch	0.297 mm x 0.297 mm
Plug & Play	DDC 2B Compliance
OSD (On Screen Display)	Auto Tune, Brightness, Contrast, Clock, Phase, H-position, V-position, Recall
Touch Technology	5 Wire Resistive, Capacitive Technology
Touch Interface	Dual (Serial/USB)
Operating Environment	0°C-40°C (32°F-104°F) 10%-80% (no condensation)
Storage Conditions	-20°C-60°C (-4°F-140°F) 10%-90% (no condensation)
Product Dimensions	343mm (width) 363mm (height) 185mm (depth)
Package Dimensions	472mm (width) 444mm (height) 208mm (depth)
Weight Gross	15.8 Lbs (7.16 Kgs)
Stand Style	U-Mount Cable Management Base
Mounting Option	Desktop, Bolt Down & VESA Mountable
Monitor Tilting	160°
Color	Black
Viewing Angle	-75°/+75°/-60°/+60°(L/R/U/D)
MTBF	50,000 Hours
PC Video Interface	Analog RGB (VGA)
Horizontal Scan Rate	30-60 Khz
Vertical Scan Rate	56-75 Hz
Display Mode	VGA 640 x 480 (60/66/70/72/75 Hz) SVGA 800 x 600 (60/70/72/75 Hz) XGA 1024 x 768 (56/70/75 Hz)
Front Control	On/Off with LED, Menu Auto Tune, Adj. (+/-)
Electrical Power	Adapter Input 100-240 VAC, 50-60 Hz 1.5A Adapter Output 12VDC, 3.33A (C+)
Power Consumption	30W (Max)
Certification	FCC, CE, UL, MIC

### Applications

- Retail/Hospitality
- Home/Office
- Medical/Education

Optional Parts	Magnetic Card Reader (MSR)	US-MSR-3TRK-U
	Magnetic Card Reader Bracket	U09-A15178



Elite Digital Solutions Inc.  
128 Adesso Drive, Unit 2  
Vaughan, Ontario, Canada L4K 3C3  
Office: 905-738-8428  
Fax: 905-738-1004  
Toll Free: 1-877-738-8428  
Email: sales@elitedigitalsolutions.com  
www.elitedigitalsolutions.com